

**Certification
Issued Under the Authority of the
Federal Communications Commission
By:**

**MiCOM Labs
575 Boulder Court
Pleasanton, CA 94566**

**Date of Grant: 07/22/2022
Application Dated: 07/22/2022**

**Doodle Labs (SG) Pte Ltd
150 Kampong Ampat, KA Center, Suite 05-03
Singapore, 368324
Singapore**

Attention: Dr Aaron Do , Senior RF Engineer

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AG87RM-3625
Name of Grantee: Doodle Labs (SG) Pte Ltd
Equipment Class: Citizens Band Category A and B Devices
Notes: Smart Radio - CBRS
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
EP MO	96	3555.0 - 3695.0	0.387	0.015 PM	1M97G1D
EP MO	96	3555.0 - 3695.0	0.344	0.015 PM	3M45G1D
EP MO	96	3555.0 - 3695.0	0.366	0.015 PM	5M62G1D
EP MO	96	3555.0 - 3695.0	0.435	0.015 PM	2M71D1D
EP MO	96	3555.0 - 3695.0	0.43	0.015 PM	4M66D1D
EP MO	96	3555.0 - 3695.0	0.408	0.015 PM	7M66D1D
EP MO	96	3555.0 - 3695.0	2.742	0.015 PM	1M97G1D
EP MO	96	3555.0 - 3695.0	2.432	0.015 PM	3M45G1D
EP MO	96	3555.0 - 3695.0	2.594	0.015 PM	5M62G1D
EP MO	96	3555.0 - 3695.0	3.076	0.015 PM	2M71D1D
EP MO	96	3555.0 - 3695.0	3.041	0.015 PM	4M66D1D
EP MO	96	3555.0 - 3695.0	2.891	0.015 PM	7M66D1D

Single Modular Approval. Power output is EIRP. This transmitter operates as Category A and Category B CBSD. Category B CBSD is limited to professional installation and outdoor operations. OEM integrators must be provided with antenna installation instructions. The OEM integrators must be instructed to ensure that the end user has no manual instructions to remove or install the device. OEM integrators and end-users must be provided with transmitter operation conditions for satisfying RF exposure compliance. Only the antenna tested with the device or similar antennas with equal or lesser gain may be used with this transmitter. The antenna used with this transmitter must be installed to provide a minimum separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi-transmitter product procedures. End-users must be provided with operating procedures for satisfying RF exposure compliance.

EP: Output power is Effective Isotropic Radiated Power (EIRP)

MO: This Multiple Input Multiple Output (MIMO) device was evaluated for multiple transmitted signals as indicated in the filing.